

AUTOMATIC SENSOR URINAL FLUSHER


C - 998A (Electrically Operated) /

C - 998B (Battery Operated)




SPECIFICATIONS

- Concealed type, Stainless steel panel with chrome plated zinc alloy outer rim and stainless steel control box
- All-in-One brass solenoid valve
- Fully automatic with IR sensors
- Built-in water flow regulator valve allows water to be adjusted and turned off as desired. Built-in water filter unit protect solenoid valve
- Electronic control components are filled with resins and sealed by ultrasound process to give moisture free life
- Water inlet diameter 1/2" (inch)
- 230 Volts, A/C single phase for C998A
- Use of four "AA" size ALKALINE 1.5 V batteries (DC6V) for C998B
- Sensing range adjustable: 30 80 cm



Urinal Flusher with water inlet on the upper side



Urinal Flusher with water Inlet on the rear side

Marketed by

(A Unit of Kalpi Engineers Pvt. Ltd.)




AUTOMATIC SENSOR URINAL FLUSHER

C - 950B (Battery Operated)

SPECIFICATIONS

- Wall mount type, Fully chrome plated brass body
- Fully automatic with IR sensors
- Built-in water flow regulator valve allows water to be adjusted and turned off as desired. Built-in water filter unit protect solenoid valve
- Electronic control components are filled with resins and sealed with ultrasound process to give moisture free life.
- Water inlet diameter 1/2" (inch)
- Use of four "AA" size ALKALINE 1.5 V batteries (DC6V)
- Sensing range adjustable: 30 80 cm




AUTOMATIC SENSOR TOILET FLUSHER

C - 904B (Battery Operated)

SPECIFICATIONS

- Exposed type
- Fully chrome plated brass body and brass solenoid valve
- AUTOMATIC and MANUAL operation with IR sensors
- Built-in water filter unit protect solenoid valve
- One inch large caliber electromagnetic valve gives strong and intense flushing
- Electronic control components are filled with resins to give moisture free life.
- Water inlet diameter 1" (inch)
- Use of four "AA" size ALKALINE 1.5 V batteries (DC6V)
- Sensing range adjustable: 30 80 cm



Marketed by

(A Unit of Kalpi Engineers Pvt. Ltd.)

Authorised Dealer:

Authorised Dealer:

No. 1005. A SEX Santhur. Systems,

No. 1005. The State Authorise colony Nanagaristists, Chennal - 600 0114, Tamilhadu, inclin Tele; Fax.048 6505061. Lice: #80.0505061. Lice: #80.0506






AUTOMATIC SENSOR TOILET FLUSHER

C - 913B (Battery Operated)

SPECIFICATIONS

- Concealed type, Stainless steel panel with stainless steel outer rim and stainless steel control box. All-in-One brass solenoid valve
- AUTOMATIC and MANUAL Operation
- Built-in water flow regulator valve allows water to be adjusted and turned off as desired. Built-in water filter unit protect solenoid valve
- One inch large caliber electromagnetic valve gives strong and intense flushing
- Electronic control components are filled with resins to give moisture free life
- Water inlet diameter 1" (inch)
- Use of four "AA" size ALKALINE 1.5 V batteries (DC6V)
- Sensing range adjustable: 30 80 cm




AUTOMATIC SENSOR URINAL FLUSHER

- C 988A (Electrically Operated)
- C 988B (Battery Operated)

SPECIFICATIONS

- Concealed type, Stainless steel panel with stainless steel / ABS chrome plated outer rim and stainless steel control box
- All-in-One brass solenoid valve
- Fully automatic with IR sensors
- Built-in water flow regulator valve allows water to be adjusted and turned off as desired. Built-in water filter unit protect solenoid valve
- Electronic control components are filled with resins and sealed by ultrasound process to give moisture free life
- Water inlet diameter 1/2" (inch)
- 230 Volts, A/C single phase for C988A
- Use of four "AA" size ALKALINE 1.5 V batteries (DC6V) for C988B
- Sensing range adjustable: 30 80 cm



Urinal Flusher with water inlet on the rear side

Marketed by

(A Unit of Kalpi Engineers Pvt. Ltd.)